



VC-FRO-460

58° Azimuth Beam, 50.5 inches

Directing our energies for you.



824-896 MHz Vpol

Electrical Specifications

Frequency	824-896 MHz
Polarization	Vertical
Gain	13.4 dBd
Horizontal Beam (3dB Points)	58°
Vertical Beam (3dB Points)	14.5°
Elect. Downtilt Range, 2° Increments	0-6°
VSWR / Return Loss	<1.40:1 / 15.6 dB
VSWR Opt "i" / Return Loss	<1.50:1 / 14.0 dB
Front-to-Back at Horizon	>30 dB
Upper Side Lobe Suppression	<-18 dB
Impedance	50 Ohms
Power Input Per Connector	500 CW at 800 MHz
Intermodulation (2x20W)	<-150 dBc


Mechanical Specifications

Input Connector (female)	Back 7/16 DIN (silver finish) or w/bot. opt.
Antenna Dimensions (LxWxD)	50.5 x 14.6 x 8.0 in. (1283 x 371 x 203mm)
*Antenna Weight	22 lbs
Bracket Weight	13.2 lbs
Lightning Protection	Direct Ground
RF Distribution	Printed Microstrip Substrate
Radome	Ultra High-Strength Luran
Weatherability	UV Stabilized, ASTM D1925
Radome Water Absorption	ASTM D570, 0.45%
Environmental	MIL-STD-810E
Wind Survival	150 mph
Front Wind Load @ 100MPH	127 lbs
Equivalent Flat Plate @ 100MPH	2.59 sq-ft. (c=2)
Mounting Brackets	Fits 3.5 Inch Max. O.D. Pipe
Mechanical Downtilt Range	0-12°
Clamps/Bolts	Hot Dip Galvanized Steel/Stainless Steel



Available with Opt "i"

- The Opt "i" antenna option provides Integrated Diplexers that reduce mainline cables and eliminate separate external devices.



1 Year Warranty

Recommended Connector Coupling Torque
7/16 DIN: 220-265 lbf-in (25-30 N-m)

Return Loss at pass-thru port into 50Ω load ≥ 17.7 dB

Ordering Information & Options

- VC-FRO-460-x "-x" is a placeholder for the built-in fixed electrical downtilt in degrees, set to 0, 2, 4, 6
- VC-FRO-460-xi to add the Opt "i" option for integrated diplexers, add "i" to model number
- VC-FRO-460-xi-bot for bottom mounted connectors, add "-bot" (otherwise antenna comes standard with back mounted connectors)
- VC-FRO-460-xi-bot-j# add a "j#" to add a 1/2" RF cable, where "#" is the cable length, "j2" is 2 meters, "j4" is 4 meters, "j6" is 6 meters...

*Antenna Weight may vary slightly with options such as back or bottom connector and integrated diplexers.